FLINN SCIENTIFIC

Data Tables

Part 1.

	Trial 1	Trial 2
Measured melting point	°C	°C
Literature melting point	°C	°C

Part 2.

Mass of crucible and cover	g
Mass of crucible, cover, and alum crystals	g
Mass of alum crystals	g
Mass of crucible, cover, and alum after heating 1	g
Mass of crucible, cover, and alum after heating 2	g
Mass of water driven off	g
Mass of anhydrous alum, AlK(SO ₄) ₂	g
Moles H ₂ O	
Moles AlK(SO ₄) ₂	
Mole ratio; moles H ₂ O/moles AlK(SO ₄) ₂	

Part 3.

Mass of alum	g
Mass of filter paper + $BaSO_4$	g
Mass of filter paper + BaSO ₄ (2nd weighing)	g
Mass of filter paper	g
Mass of BaSO ₄	g
Mass of sulfate in the precipitate	g
Experimental % sulfate in alum	%
Theoretical % sulfate in alum	%
Percent error	%

© 2019, Flinn Scientific, Inc. All Rights Reserved. Reproduction permission is granted from Flinn Scientific, Inc. Batavia, Illinois, U.S.A. No part of this material may be reproduced or transmitted in any form or by any means, electronic or mechanical, including, but not limited to photocopy, recording, or any information storage and retrieval system, without permission in writing from Flinn Scientific, Inc.

Calculations and Analysis

Part 1.

1. Find the literature value for the melting point of aluminum potassium sulfate and enter this value in the Part 1 Data Table.

Part 2.

- 1. From the mass of anhydrous alum remaining in the crucible after heating and its formula, $AlK(SO_4)_2$, calculate the moles of anhydrous alum in the original sample. Enter this value in the Part 2 Data Table.
- 2. From the mass of water driven off from the sample and the molar mass of water, calculate the moles of water in the original sample. Enter this value in the Part 2 Data Table.
- 3. Calculate the mole ratio of water to anhydrous alum in the sample. Record this value in the Part 2 Data Table.

Part 3.

- 1. Calculate the percent sulfate in barium sulfate.
- 2. Calculate the mass of sulfate in the precipitated barium sulfate. Record this value in the Part 3 Data Table.
- 3. Calculate the percent sulfate in the alum sample. Record this value in the Part 3 Data Table.
- 4. Calculate the theoretical percent sulfate in alum, AlK(SO₄), H₂O. Record this value in the Part 3 Data Table.
- 5. Calculate the percent error in the determination of sulfate ion in alum.

Post-Laboratory Review Questions

1. Why must objects be cooled before their mass is determined on a sensitive balance?

2. Comment on the results of the different tests used to verify that the sample tested was alum.

3. What other tests could be used to verify the composition of alum?